



Certificate of Compliance

This certificate is issued for the following:

Pipe Fittings for Aboveground Fire Protection Systems

(see attached product table)

Prepared for:

Shandong Zhihua Pipe Industry Co Ltd
Zhang Jia Village, Fang an Subdistrict,
Fangzi District , Shandong Province
262113,
China

Manufactured by:

Shandong Zhihua Pipe Industry Co Ltd
Zhang Jia Village, Fang an Subdistrict,
Fangzi District , Shandong Province
262113,
China

FM Approvals Class: 1920

Approval Identification: 0003054850

Superseded by: RR211904

Date Approved: May 10, 2016

Date Approved: December 6, 2017

To verify the availability of the Approved product, please refer to www.approvalguide.com

Said Approval is subject to satisfactory field performance, continuing Surveillance Audits, and strict conformity to the constructions as shown in the Approval Guide, an online resource of FM Approvals.

A handwritten signature in black ink that reads 'D.B. Fuller'.

David B. Fuller
VP, Manager of Fire Protection
FM Approvals
1151 Boston-Providence Turnpike
Norwood, MA 02062 USA



Member of the FM Global Group



Certificate of Compliance

Shandong Zhihua Pipe Industry, Pipe Fittings

<i>Product Designation</i>	<i>Fitting Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Rated Working Pressure, psi (kPa)</i>	<i>Remarks</i>
XGQT01	90° Elbow	33.7, 42.4, 48.3, 60.3, 73.0, 76.1, 88.9, 108, 114.3, 133, 139.7, 159, 165.1, 168.3, 219.1, 273.0, 323.9	300 (2070)	c
XGQT02	45° Elbow	33.7, 42.4, 48.3, 60.3, 73.0, 76.1, 88.9, 108, 114.3, 133, 139.7, 159, 165.1, 168.3, 219.1	300 (2070)	c
XGQT09	22.5° Elbow	114.3, 165.1, 219.1	300 (2070)	c
XGQT9	11.25° Elbow	114.3, 165.1, 219.1	300 (2070)	c
XGQT03	Equal Tee	33.7, 42.4, 48.3, 60.3, 73.0, 76.1, 88.9, 108, 114.3, 133, 139.7, 159, 165.1, 168.3, 219.1, 273.0, 323.9	300 (2070)	c
XGQT04	Reducing Tee (Grooved Outlet)	60.3 x 33.7, 42.4, 48.3 73.0 x 42.4, 48.3, 60.3 76.1 x 48.3, 60.3 88.9 x 48.3, 60.3, 73.0, 76.1 108 x 76.1, 88.9 114.3 x 60.3, 73.0, 76.1, 88.9 139.7 x 60.3, 76.1, 88.9, 114.3 159 x 76.1, 88.9, 108, 114.3 165.1 x 60.3, 76.1, 88.9, 114.3, 139.7 168.3 x 60.3, 73.0, 76.1, 88.9, 114.3 219.1 x 114.3, 139.7, 159, 165.1, 168.3	300 (2070)	c
XGQT04S	Reducing Tee (Threaded Outlet)	60 x 33.7, 42.4, 48.3 73.0 x 42.4, 48.3, 60.3 76.1 x 33.7, 42.4, 48.3, 60.3 88.9 x 33.7, 42.4, 48.3, 60.3, 76.1 108 x 76.1, 88.9 114.3 x 33.7, 42.4, 48.3, 60.3, 73.0, 76.1, 88.9 139.7 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 159 x 76.1, 88.9 165.1 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 168.3 - 33.7, 42.4, 48.3, 60.3, 73.0, 88.9 219.1 x 76.1, 88.9	300 (2070)	b, c
XGQT07	Equal Cross	60.3, 73.0, 76.1, 88.9, 114.3, 139.7, 159, 165.1, 168.3, 219.1	300 (2070)	c
XGQT7	Reducing Cross (Grooved Outlet)	139.7 x 114.3 165.1 x 114.3	300 (2070)	c



Member of the FM Global Group



Certificate of Compliance

<i>Product Designation</i>	<i>Fitting Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Rated Working Pressure, psi (kPa)</i>	<i>Remarks</i>
XGQT7S	Reducing Cross (Threaded Outlet)	114.3 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 139.7 x 42.4, 48.3, 60.3, 76.1, 88.9 165.1 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9	300 (2070)	b, c
XGQT06	End Cap	33.7, 42.4, 48.3, 60.3, 76.1, 88.9, 114.3, 139.7, 165.1, 168.3, 219.1	300 (2070)	c
XGQT5	Concentric Reducer	60.3 x 33.7, 42.4, 48.3 73.0 x 33.7, 42.4, 48.3 76.1 x 33.7, 42.4, 48.3, 60.3 88.9 x 33.7, 42.4, 48.3, 60.3, 73.0, 76.1 108 x 76.1, 88.9 114.3 x 60.3, 73.0, 76.1, 88.9 133 x 108, 114.3 139.7 x 60.3, 76.1, 88.9, 114.3 159 x 60.3, 76.1, 88.9, 108, 114.3, 133 165.1 x 60.3, 76.1, 88.9, 114.3, 139.7 168.3 x 60.3, 73.0, 76.1, 88.9, 114.3, 139.7 219.1 x 60.3, 76.1, 88.9, 114.3, 139.7, 165.1, 168.3	300 (2070)	c
XGQT5S	Concentric Reducer (Threaded Outlet)	60.3 x 33.7, 42.4, 48.3 73.0 x 33.7, 42.4, 48.3, 60.3 76.1 x 33.7, 42.4, 48.3, 60.3 88.9 x 33.7, 42.4, 48.3, 60.3, 73.0, 76.1 108 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 114.3 x 33.7, 42.4, 48.3, 60.3, 73.0, 76.1, 88.9 139.7 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 159 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 165.1 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 168.3 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9 219.1 x 33.7, 42.4, 48.3, 60.3, 76.1, 88.9, 114.3	300 (2070)	b, c
XGQT05	Eccentric Reducer	165.1 x 88.9, 114.3 219.1 x 114.3, 139.7, 165.1	300 (2070)	c
XGQT8	Flange Adapter (Grooved Outlet)	60.3, 73.0, 76.1, 88.9, 108, 114.3, 133, 139.7, 159, 165.1, 168.3, 219.1	300 (2070)	a, c

Remarks:

- a. Supplied with Class 125 Flanges
- b. Threads per ANSI B1.20.1 - 1983
- c. Available with Cut Grooves



Member of the FM Global Group